

Specification and Data Sheet

MODEL NO. 5-SB-H

MODEL NO. 5-SB-H HDG

1. **Product Name:** PILLOW BLOCK PIPESTAND MODEL NO. 5-SB-H or 5-SB-H HDG
2. **Design Emphasis:** The 5-SB-H HDG and related hangers have been designed specifically for 1" to 5" gas piping, conduit and water piping of the same size. The versatility of the design for this product enables it to expand to hold any number of pipe running along the roof for maximum efficiency and cost savings to customers, contractors, and owners. Thus, this pipehanger product can be used to hold one pipe across and at varying heights above the roof. See below.
3. **Manufacturer:** MIRO INDUSTRIES, INC., 844 South 430 West, Suite 100, Heber City, Utah 84032
Phone (800) 768-6978
Fax (800) 440-7958
4. **Product Description:** A "roller-bearing", "clevis hanger", or "band hanger" pipe support hanger, used to support roof mounted gas pipes, HVAC piping, electrical conduit, solar piping and other mechanical piping. Unique design absorbs thermal expansion and contraction of pipes thus preventing damage to the roof membrane. Pipes rest on a polycarbonate or steel roller, clevis hanger or band hanger. The pipe support base and all metal parts are made of stainless steel or hot-dip galvanized steel. Pipestand will accommodate up to a 5" nominal or "trade" size pipe or up to 6" outside diameter pipe.
5. **Product Performance:** The roller or clevis hanger system serves to keep the pipestand hanger system directly over and beneath the pipe without binding and allows for some lateral expansion of the piping system. The base is gently rounded to prevent gouging the roof membrane.
6. **Compatibility:** Pillow Block Pipestands are recommended for use on and compatible with all current types of decking and with all commonly used built-up and single-ply roofing membranes where roof-mounted pipes occur. With heavier loads it is prudent to use a MIRO support pad or traffic pad to further protect the roof membrane.
7. **Load Weight:** Maximum load weight not to exceed 116 lbs. per MIRON TPC™, polycarbonate or hot-dip galvanized pipestand.
8. **Composition and Materials:** The pipestand consists of four major components: (1) Either one roof deck base made of 16-gauge metal or a MIRON TPC™ or polycarbonate base which sets upon the roof membrane; (2) All-thread vertical supports of 1/2" diameter which rest upon and are connected to the one base; (3) A top strut supported by the all-thread which is 1-5/8" square or 1-5/8" by 13/16"; and (4) A hanger system consisting of a steel clevis or band hanger or roller system suspended from the all-thread and strut assembly.
9. **Size:** The Pillow Block Pipe Stand Model 5-SB-H is made as follows: The deck base is 12" by 16" (HDG) or 16" by 18" (P), has a cradle width which allows up to 10-3/4" between the all-thread assembly, and can adjust in height to support pipe from a low of 5" to a high of 18" from bottom of pipe support.
10. **Adjustable Height:** The model 5-SB-H and its related configurations allow adjustable height as desired or required by the code or roof system. Each model can be configured to allow plus or minus height above the roof up to 18". Purchasers should specify desired heights upon ordering the pillowblock hangers.
11. **Installation:** (1) Center the pipestand beneath the pipe so that the cradle allows the pipe to be squarely over and through the roller or clevis hanger of the pipestand. (2) Adjust the pipestand to the desired height and to even load with other pipestands. Make certain the horizontal support strut is level. (3) Set the pipe in the clevis hanger without dropping or causing undue impact. An additional sheet of roofing material, a MIRO Deck Plate or MIRO Support Pad should be installed beneath the pipestand. For built up roofs, all loose aggregate from an area 2" larger in width and length than the base should be removed from the area directly beneath the pipestand and then follow the installation directions set forth above. Care should be taken to install each pipestand so it supports a proportional and equal amount of weight at each pipestand.
12. **Spacing:** Manufacturer's recommended spacing is not to exceed 10 foot centers depending upon the load. Do not exceed specified load weight and make certain each pipestand is adjusted in height to even load at all pipestands. Support spacing is not to exceed the maximum spacing required in the pipe specifications where applicable.
13. **Availability:** Pillow Block Pipestands are marketed throughout the United States through representatives and distributors.
14. **Maintenance:** Normally maintenance is not required. Semi-annual inspection is required to check pipestand position and set pipe alignment, weight distribution and improper installation which may cause pipestand damage or failure.
15. **Technical Services:** Please call MIRO INDUSTRIES, INC.: (800) 768-6978 or visit our website www.miroind.com for technical information and for graphic and CAD drawing downloads.